

easyTymp

Handheld Middle Ear Analyzer – Plus Version

The easyTymp comes with a Plus

Very Fast Middle Ear Measurements

The easyTymp is the ideal handheld device for middle ear screening tests. It performs reliable tympanometry as well as ipsi- and contralateral reflex tests within seconds.

Test Protocols

All available test protocols can be easily selected with one hand. Available test protocols: tympanometry with 226 Hz and ipsi- and contralateral reflexes (automatic or single intensity). The optional high frequency probe tone of 1 kHz is ideal for providing reliable results when testing infants.

Extensive Storage

The internal memory of the easyTymp Plus Version stores more than 1000 measurements. With the impedance software, data can also be transferred to a PC.

easyTymp Plus Version Cradle

The optional cradle serves as a docking station and re-charger and is ready to insert the eartipbox.

Features at a glance

- Very fast and reliable impedance measurements
- Probe tone 226 Hz, optional high frequency probe tone 1 kHz
- Reflex frequencies 500 Hz, 1 kHz, 2 kHz, 4 kHz (ipsi- and contralateral)
- Automatic tests – self-explanatory to use
- Full color, high resolution display
- Stores more than 1000 measurements



Technical Data

TYMPANOMETRY

Probe Frequency	226 Hz \pm 1%, 85 dB _{SPL} in 2 cm ³
High Frequency	1000 Hz \pm 1%, 69 dB _{SPL} in 2 cm ³
Pressure Range	-400 to +200 daPa
Accuracy of Pressure	\pm 5% or \pm 10 daPa
Volume Range	0.1 to 8.0 ml
Compliance Range	0.1 to 8.0 ml at 226 Hz 0.1 to 15.0 mmho at 1000 Hz
Test Time	< 6 seconds

ACOUSTIC REFLEXES

Test Frequencies	500, 1000, 2000, 4000 Hz \pm 3%
Test Method	Ipsi- and contralateral
Intensities Reflexes	70 to 100 dB _{HL}
Intensity Settings	Automatic or single intensity

OPT. HIGH FREQUENCY	Tymp 1 kHz;
	Tymp 1 kHz + Auto Reflex;
	Tymp 1 kHz + Reflex 80 dB BB

GENERAL

Memory	1 curve per ear and test
Storage	> 1000 measurements
Display	Full color graphic LCD-Display
Dimensions / Weight	W x D x H: 80 x 300 x 70 mm / 427 g


OPTIONAL CRADLE

Dimensions	W x D x H: 150 x 295 x 110 mm
Power	100 - 240 VAC, 50/60 Hz

OPTIONAL PRINTER

Type	2 inch thermal dot matrix
Weight	197 g
Data Transfer	Wireless

STANDARDS

IEC 60601-1, Class II, Type B	
IEC 60601-1-2, IEC 60645-5	
according to medical directive 93/42/EEC	

STANDARD COMPONENTS

easyTymp Plus Version handheld unit, contra probe (length 140 cm), contralateral earphone CIR55, probe tip replacement, rechargeable battery power supply unit for handheld unit, eartip box with eartips and eartip removal-tool, test cavity, carrying case, impedance software

OPTIONAL ACCESSORIES

Contralateral headphone DD45C, license for high frequency probe tone of 1 kHz, cradle, power supply unit and additional rechargeable battery, wireless thermal printer, wall mount kit for docking station

SANIBEL

Sanibel™

We highly recommend to use Sanibel disposables in order to guarantee optimal test results.

Specifications are subject to change without notice.

<div>Standard Components</div>	 <p>easyTymp device</p>	 <p>Shoulderbox with contra probe and CIR 55</p>	 <p>Eartip box with eartips</p>	 <p>Carrying case</p>	 <p>Impedance Software</p>
	<div>Optional Accessories</div>	 <p>Contralateral headphone DD45C</p>	 <p>Cradle</p>	 <p>Wireless thermal printer</p>	

MAICO Diagnostics GmbH

Sickingenstr. 70-71 · 10553 Berlin · Germany
Tel.: +49 30/70 71 46-50 · Fax: +49 30/70 71 46-99
sales@maico.biz · www.maico.biz

представител за България
Илан Медицинска Апаратура ООД
София, бул. „Джеймс Баучер“ № 76А
Hill Tower Business Center et. 1
тел. 070017373
E-mail: office@ilan.bg Web: www.ilan.bg